

# AsCARD Green



<b>ECG signals</b>	12 standard leads according to Einthoven, Goldberg, Wilson and Cabrer
<b>Working mode</b>	automatic and manual
<b>Printout</b>	<ul style="list-style-type: none"> <li>• 1/3 channels</li> <li>• settable printout accuracy – thickness of printed curve lines</li> </ul>
<b>Analysis and interpretation</b>	<ul style="list-style-type: none"> <li>• automatic analysis and interpretation in compliance with EN 60601-2-51 (CSE database)</li> <li>• depends on age and gender of a patient</li> </ul>
<b>Heart pacemaker detection</b>	<ul style="list-style-type: none"> <li>• detection of heart pacemaker peaks</li> <li>• acoustic signalling of detected beats</li> </ul>
<b>Functional features</b>	<ul style="list-style-type: none"> <li>• graphical menu displayed on a screen for easy operation using keyboard</li> <li>• multilingual menu</li> <li>• continuous HR measurement presented on a screen</li> <li>• device adapted to direct operation on an open heart</li> <li>• signalisation of accumulator voltage reduction</li> <li>• signalisation of accumulator charging</li> <li>• INOP signalisation independent for each electrode</li> </ul>
<b>Display</b>	<ul style="list-style-type: none"> <li>• graphical 240x128 screen</li> <li>• presentation of 1/3/6/12 leads on a screen</li> </ul>
<b>Keyboard</b>	membrane alphanumeric keyboard with functional keys
<b>Sensitivity</b>	2.5/5/10/20 mm/mV

# AsCARD Green

<b>Speed</b>	5/10/25/50 mm/s
<b>Filters</b>	<ul style="list-style-type: none"> <li>contour line filters; filters available: 0.15 Hz, 0.45 Hz, 0.75 Hz, 1.5 Hz</li> <li>mains disturbance filter – 50 Hz, 60 Hz</li> <li>muscular disturbances filter – 25 Hz, 35 Hz, 45 Hz</li> </ul>
<b>Paper</b>	<ul style="list-style-type: none"> <li>Easy load – automatic paper loading system</li> <li>thermoactive, wax and dust free</li> <li>58 mm wide</li> </ul>
<b>Power supply</b>	<ul style="list-style-type: none"> <li>main supply 100-240 V, 47-63 Hz</li> <li>internal accumulator with charger, 6 V/1.3 Ah to perform 60 automatic examinations</li> </ul>
<b>Safety norms</b>	<ul style="list-style-type: none"> <li>protection against electric shock (EN 60601-1) – Class II device</li> <li>CF type parts resistant to defibrillation</li> <li>device class and group acc.to CISPR-11 – Class A, Group 1</li> <li>medical device class – IIa (rule 10)</li> <li>IP protection class – IP X0</li> <li>operation safety – EN 60601-1, EN 60601-2-25</li> <li>electromagnetic compatibility – EN 60601-1-2</li> </ul>
<b>Dimensions</b>	(LxWxH) 255x195x69 mm
<b>Weight</b>	< 1.3 kg
<b>Gross weight/packing dimensions</b>	3.2 kg/(LxWxH) 350x245x130 mm
<b>Standard accessories</b>	<ul style="list-style-type: none"> <li>patient cable KEKG30</li> <li>suction electrodes EPP – set of 6</li> <li>clamp electrodes EKK – set of 4</li> <li>ECG gel – 250 g</li> <li>ECG paper RB1 – 1 pc</li> <li>supply cable</li> </ul>
<b>Optional accessories</b>	<ul style="list-style-type: none"> <li>safety carry bag WMB5</li> <li>ECG paper RB1</li> <li>trolley WB5</li> </ul>
<b>Certificates</b>	<ul style="list-style-type: none"> <li>CE 0197</li> <li>EN ISO 9001</li> <li>EN ISO 13485</li> <li>MDD 93/42/EEC</li> <li>CFS</li> </ul>