

SeQual® Eclipse™ 5

PORTABLE OXYGEN CONCENTRATOR

OXYGEN WITH NO LIMITS

The SeQual® Eclipse 5 is the latest generation of the original continuous flow portable oxygen concentrator. With new robust components that are more reliable than ever, the Eclipse™ 5 combines portability with unmatched clinical efficacy to treat patients of any disease state at any activity level.

- **The Most O₂ to Treat the Most Users**

Producing up to 3.0 LPM continuous flow and with pulse settings 1-9 with a bolus size up to 192 mL, the highest of any concentrator, the Eclipse™ 5 can cover the most users and give them unlimited ambulation.

- **A True Non-Delivery Solution**

The Eclipse™ 5 is robust enough to run 24/7 and can be used by a patient during sleep, at home, on the go, and on the road – an all-in-one oxygen solution.

Continuous flow options eliminate the worry of desaturation during sleep, and the high pulse output allows even the most difficult-to-treat patients to be active with a portable device and lengthy battery life.

- **Unmatched Clinical Features**

Featuring autoSAT® technology that detects the user's breath rate and automatically adjusts the motor speed to ensure oxygen is always delivered with every breath. This helps to maintain consistent FiO₂, even in high flow patients.

The Eclipse™ 5 allows oxygen delivery to be tailored to each individual user for the best therapy. Both sensitivity and bolus rise time can be adjusted to ensure proper treatment.



PROVIDER FEATURES

- Time-proven reliability and 24/7 ruggedness
- Ideal for travel and hospital discharge programs
- Diagnostic alarm codes for easier service calls
- Bill both E1390 & E1392 codes
- O₂ monitor standard on all units
- A true 24/7 non-delivery option

PATIENT FEATURES

- Run on AC, DC or battery power
- In the car – all flow rates available and battery will recharge \leq 2 LPM
- 2 hours battery at 2 LPM with single battery
- Over 5 hours of battery duration at 2 pulse
- Removable rolling cart with adjustable handle.
- FAA Approved

CLINICAL FEATURES

- Proprietary autoSAT™ Technology
- Adjustable sensitivity
- Adjustable bolus rise time
- Bolus sizes up to 192 mL
- Highest pulse dose of any concentrator
- Ideal for pulmonary rehab patients



SPECIFICATIONS

Continuous Flow	0.5–3.0 LPM
Pulse Flow	Settings 1–6 (16–96 mL) Settings 7–9 (128–192 mL)
Weight w/Battery	18.4 lbs (8.3 kg)
Dimensions	19.3 x 12.3 x 7.1 inches (49.0 x 31.2 x 18.0 cm)
O₂ Concentration	90% (+5.5 / -3 %)
Sound Level	40 dB(A) @ Pulse Setting 3
Operating Temp.	50°F to 104°F (10°C to 40°C)
Operating Altitude	Up to 13,123 ft (4,000 m)
Battery Duration	LPM Continuous – 2 Hours Setting 2 Pulse – 5.1 Hours
Battery Re-Charge	2–5 hours dependent upon flow
AC Power	100–240 VAC, 50–60Hz
DC Power	12 V Nominal
Power Draw	145 W @ 3 LPM, 45 W Battery Charging
Warm-Up Time	< 5 Minutes
Warranty	3 Years Eclipse 5 1 Year Battery & Accessories
Maintenance Schedule	HEPA, Air Inlet, Compressor Intake Filters – 1 Year Replacement

ORDERING INFORMATION

Eclipse™ 5 Includes: Portable Concentrator, Power Cartridge (Battery), AC Power Supply & Cord, DC Power Supply, Removable Cart, Accessory Bag, Spare Intake Filter, Nasal Cannula

6900-SEQ USA
6900LN-SEQ USA – 2 Batteries
6900AU-SEQ Australian
6900-C1-SEQ European (EN, FR, DU, ES, IT, PT, NL)
6900-C2-SEQ European (SV, DA, NO, FI)
6900-08-SEQ UK
6900-20-SEQ Swiss

other countries' power supplies may be available - contact customer service

ACCESSORIES

7082-SEQ Spare Battery
5010-SEQ Travel Case
5052-SEQ Protective Cover
5942-SEQ Wheelchair Pack
7104-SEQ Cart
5220-SEQ Accessory Bag
5991-SEQ DC Power Supply

7112-SEQ Desktop Charger (US)
20554079 Desktop Charger (EU)
20554077 Desktop Charger (UK)
Cords Included

5941-SEQ AC Power Supply (US)
20553100 AC Power Supply (EU)
20553098 AC Power Supply (UK)
Cord Included


CAIRE®
 A Chart Industries Company

2200 Airport Industrial Drive, Suite 500

Ball Ground, GA 30107

770.721.7759 | Toll Free 1.800.482.2473

www.CAIREMedical.com



Copyright 2016 Chart Industries
 ML-CONC0087 Rev A